

Landscape
Depot Inc.
Erosion Control Supplies

185 Walter Way Fayetteville, GA 30214
770-719-3330 770-719-3559(fax)

140 lb Woven Geotextile

Polypropylene fabric designed for ground stabilization. This engineered geotextile is stabilized to resist degradation due to ultraviolet exposure. It is resistant to commonly encountered soil chemicals, mildew and insects, and is non-biodegradable. We wish to advise that it meets the following minimum average roll values:

Property	Test Method	Minimum Average Roll Value (English)
Weight		3.0 oz/sq.yd
Grab Tensile	ASTM-D-4632	140 lb
Grab Elongation	ASTM-D-4632	20%
Mullen Burst	ASTM-D-3786	350 psi
Puncture	ASTM-D-4833	75 lb
Trap. Tear	ASTM-D-4833	75
UV Resistance	ASTM-D-4355	90% @ 500 hrs / 80% @ 3500 hrs
Permittivity	ASTM-D-4491	0.05 sec ⁻¹
Flow Rate	ASTM-D-4491	10 gal/min/ft ²

Landscape Depot, Inc. provides the woven fabric indicated above. The values listed are a result of testing conducted by an independent testing laboratory. These test results are no more than one year old when presented to the authorizing agent.